



BOCCOLE DIELETRICHE



| | Ø A | Ø B | Ø C | *M |
|-----------|------|------|------|-------|
| cod. 1000 | 27,0 | 23,0 | 32,5 | 18-22 |
| cod. 1010 | 32,0 | 25,0 | 32,5 | 22-27 |
| cod. 1020 | 38,5 | 34,5 | 37,5 | 27-32 |

*Dimensione della vite

Boccole in PA6 con carica fibra vetro, elettricamente isolante, applicabile a piastre e tirafondi

| Campione N. | D ₁ (mm) | D ₂ (mm) | H (mm) | Spessore (mm) | Spessore (mm) | h (mm) |
|-------------|---------------------|---------------------|--------|---------------|---------------|--------|
| 1 | 38,7 | 34,7 | 37,5 | 1,98 | 1,85 | 11 |
| 2 | 38,5 | 34,5 | 37,6 | 1,97 | 1,89 | 11 |
| 3 | 37,0 | 33,1 | 32,6 | 1,94 | 1,91 | 11 |
| 4 | 37,0 | 33,1 | 32,6 | 1,95 | 1,92 | 11 |
| 5 | 26,95 | 23,1 | 32,6 | 1,91 | 1,89 | 11 |
| 6 | 26,95 | 22,9 | 32,6 | 2,00 | 1,97 | 11 |

INSERTI PER TRAVERSINE

INSERTO Ø 60 x 180



cod. 1500
Inserto



cod. 1510
Inserto



cod. 1515
Vite



cod. 1520 Ø 60 x 180
per conci e casseri